

**2008 Florida Canyon Project Drilling Results**

Hole	Width	Interval	Pb %	Zn %	Ag g/t	Pb+Zn
V-44  including and and	1.0	130.6-131.6	6.57	16.30	95.0	22.87
	0.5	178.4-178.9	0.00	7.43	0.9	7.43
	0.7	205.8-206.5	1.15	31.29	90.4	32.44
	0.3	232.1-232.4	1.37	41.96	138.0	43.33
	28.3	271.1-299.4	0.80	15.24	28.3	16.04
	9.3	271.1-280.4	2.24	37.27	70.7	39.51
	4.0	286.4-290.4	0.19	11.61	19.2	11.80
	4.0	295.4-299.4	0.22	8.51	15.5	8.73
V-45	2.0	227.7-229.7	0.97	7.57	5.6	8.54
	1.7	254-255.7	0.01	11.31	6.1	11.32
	0.5	269.2-269.7	0.02	12.45	15.2	12.47
	1.5	276.2-277.7	0.00	6.75	2.5	6.75
V-46	0.3	409.4-409.7	0.43	4.01	3.6	4.44
V-47				n/a		
V-48	1.0	304.8-305.8	0.05	16.75	0.6	16.80
V-51 including	2.3	314.4-316.7	0.05	2.26	0.5	2.31
	0.3	314.4-.14.7	0.12	9.23	0.6	9.35
V-52				n/a		
V-53				n/a		
V-54	1.6	342.7-344.3	0.30	11.16	6.1	11.46
V-56	0.4	415-415.4	0.01	25.00	0.0	25.01
V-57	0.4	169-169.4	0.00	11.00	30.7	11.00
	0.4	182.7-183.1	0.10	23.00	47.8	23.10
	1.7	191-192.7	0.03	6.06	4.6	6.09
	1.0	228.7-229.7	0.78	17.00	21.2	17.78
V-164 incl	1.0	203.3-204.3	0.08	7.02	8.3	7.11
	0.3	204-204.3	0.26	20.10	23.2	20.36
	1.8	247-248.8	0.00	11.41	10.1	11.41
	0.7	256.3-257	0.00	17.20	9.7	17.20
V49 incl. and	25.0	242.2-268.2	0.23	5.24	3.99	5.26
	9.0	242.2-252.2	0.13	10.54	5.16	9.61
	6.0	262.2-268.2	0.71	5.27	7.15	5.98
V165	1.0	107.2-108.2	0.00	3.96	0.51	3.96
	0.3	143.5-143.8	0.38	4.89	7.79	5.27
	19.0	238.5-257.5	0.81	12.82	29.41	13.64
V58	2.0	35.4-37.4	0.38	3.47	2.33	3.85

	7.3	148.1-155.4	0.12	6.13	1.54	6.25
	9.7	166.7-176.4	0.37	3.66	2.80	4.03
Incl.	1.7	166.7-168.4	0.44	12.55	8.18	13.00
and	4.3	172.1-176.4	0.61	3.18	2.73	3.79
V166	4.7	42.6-47.3	0.28	18.40	5.79	18.68
	4.0	173-177	0.25	7.81	1.77	8.05
incl.	2.0	175-177	0.48	13.77	3.36	14.25
V115			n/a			
V139			n/a			
V111			n/a			
V_130	9.0	113.5-122.5	0.95	10.17	7.35	11.12
V_113	1.0	222.2-223.2	0.01	7.64	0.76	7.64
	1.0	269.2-270.2	8.89	32.49	103.00	41.38
V_121	2.0	259.3-261.3	0.98	30.92	11.30	31.90
V_133	1.0	210.7-211.7	0.34	5.47	2.70	5.81
	2.0	215.7-217.7	0.32	2.58	5.89	2.90
V_112	7.0	199.9-206.9	1.30	5.96	12.42	7.25
V_122	1.0	314-315	0.11	3.94	1.58	4.04
V_136			n/a			
V_137			n/a			
V_109	1.3	204.9-206.2	6.17	10.35	39.80	16.52
V_128	4.7	254.5-259.2	0.66	6.54	3.47	7.20
incl.	2.7	256.5-259.2	1.12	10.27	5.62	11.40
	0.7	282.5-283.2	0.01	4.56	0.70	4.57
	0.7	286.5-287.2	0.15	10.95	2.30	11.10
V_110	3.2	173.5-176.7	4.14	24.07	52.83	28.21
	2.0	181-183	0.03	2.54	1.54	2.57
V_125	1.7	270.1-271.8	0.59	6.20	5.22	6.79
V_114			n/a			
V_87	0.7	51.2-51.9	0.01	5.49	15.40	5.50
	1.4	70.5-71.9	0.17	12.48	3.26	12.64
V_138	0.7	59.6-60.3	1.82	23.20	42.00	25.02
	2.0	239.1-241.1	0.16	13.50	3.19	13.66

V_127				n/a			
V_135				n/a			
V_134				n/a			
V_89	7.0	86.7-93.7	0.38	11.85	3.34	12.23	
	0.7	101-101.7	0.12	4.12	0.30	4.24	
V 90	0.3	72.9-73.2	3.55	1.36	23.6	4.91	
	0.3	77.3-77.6	15.10	0.33	89.2	15.43	
	0.5	89.2-89.7	4.87	16.7	26.1	21.57	
	0.7	99.2-99.9	0.01	12.95	1.21	12.96	
	0.7	105.9-106.6	0.41	16.45	7.14	16.86	
V_ 91	3.0	66.5-69.5	0.48	6.82	6.4	7.30	
	2.3	74.2-76.5	2.00	4.28	14.3	6.28	
	1.4	88.8-90.2	4.60	18.72	23.9	23.32	
V_ 92	13.4	87.9-101.3	0.21	4.60	1.4	4.81	
incl	1.0	87.9-88.9	1.17	29.30	8.9	30.47	
and	1.0	91.3-92.3	0.50	5.24	2.8	5.74	
and	1.0	100.3-101.3	0.02	4.15	0.2	4.17	
	0.3	114-114.3	25.50	13.65	0.2	39.15	
V 129	5.0	290.2-291.2	0.69	7.7	6.352	8.39	
V_ 132	0.7	192.8-193.5	2.43	9.37	13.8	11.80	
	7.1	226.8-233.9	1.29	12.18	8.9	13.48	
V 145	1.0	370.9-371.9	2.19	5.05	42.8	7.24	
	1.0	389.9-390.9	0.39	3.03	47.8	3.42	
	1.0	406.9-407.9	0.17	3.77	21.9	3.94	
V 88	1.0	96.6-97.6	0.35	3.65	1.0	4.00	
V 124	0.6	341.9-342.5	20.70	9.80	128.0	30.50	
V 123	1.0	322.5-323.5	0.64	10.36	7.7	11.01	