

2012 Underground Drilling Results
Intervals With Grade (Zn + Pb) x Thickness Greater Than 4.0
(True thickness has not been estimated for each individual intercept)

Drill Hole - (Drill Station)	From - To (m)	Interval (m)	Zinc %	Lead %	Zn + Pb %	Silver Grams/t
V-292 - (DS-1)	103.00 ---125.2	22.2	12.45	0.97	13.42	17.23
V-293 - (DS-1)	212.4-219.7	7.3	7.55	0.33	7.88	5.78
	234.7-237.7	2.7	4.26	0.13	4.39	2.99
	253.1-253.8	0.7	10.60	0.01	10.61	3.70
V-294 - (DS-1)	96.6-110.4	13.8	7.17	2.66	9.83	27.78
	114.4-115.4	1.0	8.99	0.27	9.26	15.50
	125.6-127.1	1.5	8.24	0.02	8.26	22.45
V-295 - (DS - 1)	59.6-61.5	1.9	9.66	0.17	9.83	4.55
V-296 - (DS - 1)	145.5-146.0	0.5	12.70	0.07	12.77	20.05
	384.0-385.3	1.3	9.14	0.01	9.15	1.59
V-297 - (DS - 1)	42.0-43.3	1.3	7.18	0.79	7.97	18.20
	91.5-92.3	0.8	13.10	0.07	13.17	0.25
	198.8-202.2	3.4	9.08	0.01	9.09	7.85
	210.8---267.4	56.6	22.69	1.15	23.84	31.23
V-298 - (DS - 1)	36.4-38.4	2.0	2.67	0.28	2.95	3.80
	115.5---122.9	7.4	40.05	3.68	43.73	58.99
	129.2---135.7	6.5	14.75	2.50	17.25	20.90
V-299 - (DS - 1)	59.6-60.3	0.7	5.43	0.73	6.16	14.30
	82.1---89.8	7.7	19.03	2.80	21.83	30.26
	94.3-96.3	2.0	9.97	0.18	10.15	9.94
	118.3-120.7	2.4	9.48	1.17	10.65	16.08
	122.5-127.9	5.4	3.75	0.01	3.76	2.16
	129.1-130.3	1.2	5.03	0.02	5.05	2.00
V-300 - (DS - 1)	64.8---79.3	14.5	26.57	2.15	28.72	29.46
	87.0-88.8	1.8	3.69	0.53	4.22	6.03
	112.2-112.8	0.6	30.83	0.43	31.26	7.20
	117.7-119.4	1.7	4.35	0.68	5.03	7.51
	188.3---197.0	8.7	12.87	1.41	14.28	11.14
	200.5-202.7	2.2	16.28	1.07	17.35	14.99
V-301 - (DS - 1)	51.3-51.9	0.6	12.00	0.02	12.02	1.80
	125.0-140.4	15.4	22.81	0.40	23.21	35.00
V-302 - (DS - 1)	46.0-46.7	0.7	8.21	0.01	8.22	1.10
	49.0-50.9	1.9	5.60	0.01	5.61	0.54
	63.2-64.5	1.3	6.15	0.06	6.21	2.81
	91.9---108.8	16.9	19.16	0.98	20.14	31.12
V-303 - (DS - 1)	65.4-67.4	2.0	2.16	0.00	2.16	0.94
	78.9-79.9	1.0	8.48	0.12	8.60	1.40
	84.5-85.3	0.8	7.38	0.98	8.36	19.10

	153.8-155.5	1.7	8.21	0.01	8.22	1.91
--	-------------	-----	------	------	------	------

V-354 - (DS - 1)	32.5-38.8	6.3	2.84	0.12	2.96	3.93
	177.4-180.4	3.0	19.65	0.21	19.86	22.48
	195.4---206.6	11.2	11.62	0.09	11.71	12.73
	209.1-211.1	2.0	11.02	0.01	11.03	12.24
	213.8---225.6	11.8	11.87	0.48	12.35	10.10
	260.8-263.2	2.4	11.43	0.04	11.47	23.08
	280.1-281.4	1.3	19.25	0.00	19.25	17.60
	309.9-310.6	0.7	13.20	0.02	13.22	2.80
V-355 - (DS - 1)	111.9-113.9	2.0	2.35	0.08	2.43	0.73
	116.9-120.0	3.1	4.82	1.43	6.25	7.95
	167.0-167.3	0.3	18.70	0.28	18.98	7.20
	194.2-198.8	4.6	10.42	2.11	12.53	43.68
	258.5-260.2	1.7	5.44	2.53	7.97	11.16
V-356 - (DS - 1)	141.9-143.9	2.0	2.62	0.01	2.63	3.65
	172.1-172.8	0.7	10.80	0.00	10.80	2.40
	182.2-182.5	0.3	17.70	0.01	17.71	10.30
	211.9-220.2	8.3	10.21	0.00	10.21	0.25
	229.2-241.9	12.7	5.62	0.01	5.76	3.03
V-282 - (DS - 2)	96.3-97.3	1.0	1.81	7.29	9.10	49.76
	110.0-112.0	2.0	5.94	0.02	5.96	9.90
V-283 - (DS - 2)	79.6-82.4	2.8	4.96	0.66	5.62	16.60
	97.8-106.6	8.8	5.89	0.03	5.92	25.07
	114.5-118.6	4.1	12.42	0.04	12.46	32.34
	127.3-130.2	2.9	3.57	1.02	4.59	8.82
V-284 - (DS - 2)	89.5-97.3	7.8	6.27	0.24	6.51	4.97
V-285 - (DS - 2)	113.3-114.7	1.4	20.30	7.46	27.76	54.90
V-267 - (DS - 3)	53.6-59.9	6.3	15.92	0.92	16.84	12.89
	98.8-100.1	1.3	3.92	0.83	4.75	10.68
V-272 - (DS - 6)	26.5-33.4	6.9	6.85	1.55	8.40	15.39
	36.7-42.3	5.6	12.41	2.77	15.18	37.95
	57.9-65.1	7.2	8.30	0.22	8.52	18.44
	77.4-81.4	4.0	15.26	0.01	15.27	8.24
	84.3-89.0	4.7	7.67	0.00	7.67	3.24
V-273 - (DS - 6)	29.1-37.1	8.0	11.21	0.27	11.48	20.86
	47.5-50.1	2.6	4.29	0.01	4.30	6.55
V-274 - (DS - 6)	21.5-22.3	0.8	27.30	1.75	29.05	37.10
V-275 - (DS - 6)	22.7-28.1	5.4	4.79	0.02	4.81	3.98
V-276 - (DS - 6)	21.5-25.6	4.1	13.27	0.54	13.81	24.74
	65.0-67.0	2.0	5.30	0.08	5.38	18.45
	73.6-79.9	6.3	11.42	0.71	12.13	27.49
	83.9-85.2	1.3	3.46	0.59	4.05	3.32
V-277 - (DS - 6)	51.3-53.0	1.7	3.83	0.04	3.87	2.74
	69.9-88.5	18.6	3.46	0.59	4.05	3.32

V-278 - (DS - 6)	38.4-40.3	1.9	3.60	0.00	3.60	0.87
	60.7-62.7	2.0	4.21	0.08	4.29	1.58
	80.8-84.8	4.0	7.87	1.59	9.46	4.65
	89.0-111.1	22.1	8.72	2.28	11.00	17.73
V-307 - (DS - 7)	9.8-11.8	2.0	5.18	0.07	5.25	1.60
	18.5-24.5	6.0	1.79	2.09	3.88	16.16
	27.9-36.1	8.2	5.74	0.15	5.89	4.10
	56.6-57.8	1.2	4.64	0.01	4.65	5.40
	61.2-71.9	10.7	6.05	0.02	6.07	5.31
74.8-78.5	3.7	2.72	0.00	2.72	1.79	
V-309 - (DS - 7)	32.2-41.3	9.1	8.86	0.25	9.11	14.51
V-310 - (DS - 7)	10.9-20.9	10.0	6.49	0.25	6.74	2.42
V-311 - (DS - 7)	0.0-3.0	3.0	2.89	0.60	3.49	3.11
	8.8-18.2	9.4	6.51	0.14	6.65	3.91
	45.4-47.3	1.9	2.24	0.00	2.24	2.03
	49.2-51.0	1.8	9.87	0.01	9.88	5.73
V-312 - (DS - 7)	0.0-10.3	10.3	6.03	1.37	7.40	7.63
	24.8-25.5	0.7	11.00	0.07	11.07	29.60
	43.4-48.0	4.6	6.57	1.55	8.12	14.75
	58.1-66.4	8.3	12.63	0.17	12.80	19.00
V-313 - (DS - 7)	2.1-9.4	7.3	10.32	0.83	11.15	12.72
	16.8-17.1	0.3	21.90	6.40	28.30	107.00
	83.5-85.8	2.3	2.33	0.16	2.49	3.68
	101.2-103.6	2.4	21.03	4.58	25.61	56.68
V-314 - (DS - 7)	16.5-19.1	2.6	5.60	0.56	6.16	9.67
	91.1-93.1	2.0	3.05	0.03	3.08	3.85
	97.2-98.6	1.4	5.86	0.00	5.86	3.72
	198.2-199.1	0.9	5.19	0.00	5.19	0.70
V-316 - (DS - 7)	7.9-9.9	2.0	10.58	0.02	10.60	1.45
	31.5-33.5	2.0	2.23	0.28	2.51	7.40
V-341 - (DS - 8)	79.8-89.0	9.2	1.85	0.00	1.85	1.60
V-344 - (DS - 8)	79.8-80.2	0.4	35.21	0.00	35.21	110.00
V-346 - (DS - 8)	41.9-42.2	0.3	14.40	26.30	40.70	79.50
	68.0-70.0	2.0	2.82	0.02	2.84	3.97
	108.6-110.4	1.8	6.06	0.00	6.06	3.56
	112.3-118.8	6.5	5.14	0.01	5.15	2.66
	174.1-176.1	2.0	4.14	0.13	4.27	9.96
V-347 - (DS - 8)	8.6-9.8	1.2	6.40	0.22	6.62	5.80
	151.9-152.4	0.5	36.04	0.01	36.05	47.20